



Yamaha High Thrust



Specifications	T60	T50	T25	T9.9
Engine Type	4 cyl.	4 cyl.	2 cyl.	2 cyl.
Displacement	60.8 ci (996 cc)	60.8 ci (996 cc)	30.4 ci (498 cc)	12.9 ci (212 cc)
RPM Range	5000-6000	5000-6000	5000-6000	5000-6000
Alternator Output @ W.O.T.	17A	17A	13A	6A
Compression Ratio	9.5:1	9.5:1	9.4:1	9.5:1
Fuel/Induction System	SOHC Fuel Injection	SOHC Fuel Injection	SOHC Carb	SOHC Carb
Lubrication	Wet Sump	Wet Sump	Wet Sump	Wet Sump
Ignition System	TCI Micro Computer	TCI Micro Computer	CDI Micro Computer	CDI Micro Computer
Starting System	Electric	Electric	Electric	Electric
Shaft Length	20 in.	20 in.	20 in.	20 in., 25 in.
Gear Ratio	12:28 (2.33)	12:28 (2.33)	12:29 (2.42)	13:38 (2.92)
C.A.R.B. Rating	3-Star	3-Star	3-Star	3-Star
Weight*	267 lb (121 kg)	267 lb (121 kg)	203 lb (92.0 kg)	106 lb (48 kg)
Warranty	3 Year Limited Pleasure Boat - 1 Year Limited Commercial	3 Year Limited Pleasure Boat - 1 Year Limited Commercial	3 Year Limited Pleasure Boat - 1 Year Limited Commercial	3 Year Limited Pleasure Boat - 1 Year Limited Commercial

* Weight refers to shortest shaft length available.

** Consult your dealer for optional equipment.

Specifications subject to change without notice. Consult your dealer for optional equipment.

©2010 Yamaha Motor Corporation, U.S.A.